

FF FCP250-L

Intelligent Addressable Fire Alarm Panel



Applus⁺ **EN 54-2**
EN 54-4

FEATURES

- ▶ Scalable architecture expandable from 1 to 9 loops
- ▶ Supports up to 240 addressable devices per loop
- ▶ 4.3" colour TFT touchscreen display (480 x 272 pixels)
- ▶ 32-bit microprocessor-based architecture
- ▶ User-friendly graphical interface
- ▶ Multi-level password protection
- ▶ USB data import / export functionality
- ▶ Flush or surface mounting options
- ▶ Maintenance-friendly visual alert system
- ▶ Event log memory for up to 1,000 events
- ▶ Possibility to expand up to 128 panels
- ▶ Certified to EN 54-2 and EN 54-4
- ▶ Made in Italy

ORDER DETAILS

- ▶ FF FCP250-LOOP2 - Expansion Card 2 Loops
- ▶ FF FCP250-NET - Network Card
- ▶ FF FCP250-PRT - Printer
- ▶ FF FCP250-PW - Additional Power Supply
- ▶ FF FCP250-56 - Panel Led(56 leds) for Alarm of Zones

TECHNICAL SPECIFICATIONS

Display	4.3" TFT Touchscreen, 480 × 272 pixels
Number of Loops	1 (expandable up to 9)
Programming Input / Output	Micro USB
Memory	RAM: 2 MB Flash: 512 KB EEPROM: 4 MB
Protection Rating	IP30
Operating Temperature	-5°C ~ +40°C
Storage Temperature	-40°C ~ +70°C
Dimensions	410 × 410 × 120 mm
Weight	6.1 kg

FND-DS-FFFCP250-L-EN-REV01