

## FF LSB250A

### Intelligent Addressable Sounder Beacon With Short Circuit Isolator



**Arplus<sup>+</sup>**

**EN 54-3  
EN 54-17**

#### FEATURES

- ▶ Built-in short-circuit isolator
- ▶ Voltage reading at addressed device terminals
- ▶ Addressable sounder with beacon
- ▶ Extractable terminal board for easy installation
- ▶ Deep base for easier loop wiring
- ▶ 107 dB sound output
- ▶ Glossy red ABS housing
- ▶ IP65 protection with PG7 cable glands
- ▶ Certified according to EN54-3 and EN54-17
- ▶ Made in Italy

#### TECHNICAL SPECIFICATIONS

|                       |                |
|-----------------------|----------------|
| Supply Voltage        | 18 ~ 27V       |
| Stand-by Consumption  | 130 $\mu$ A    |
| Alarm Consumption     | 27mA           |
| Absorbed Power        | 0.6W           |
| Sounder Voltage ON    | 24 V dc        |
| Sound Output          | 107dB          |
| Operation Temperature | -10°C ~ +55°C  |
| Degree of Protection  | IP65           |
| Size                  | D:100mm H:92mm |
| Humidity              | 85% RH         |

#### ORDER DETAILS

- ▶ FF LSB250A - Intelligent Addressable Sounder Beacon With Short Circuit Isolator

FND-DS-FFLSB250A-EN-REV01