

## FF MI250A-3

# Intelligent Addressable 3 Inputs Module With Short Circuit Isolator



**Applus<sup>+</sup>**

**EN 54-17  
EN 54-18**

## FEATURES

- ▶ 3 supervised input channels for auxiliary device monitoring
- ▶ Built-in short-circuit isolator
- ▶ Voltage reading at the terminals of the addressed device
- ▶ Three-colour status LED (red / green / yellow) controlled by the panel
- ▶ Rest, alarm and fault condition monitoring through balancing resistors
- ▶ Extractable terminal blocks (loop and field side)
- ▶ Compact ABS housing (matt white)
- ▶ Certified to EN 54-17 and EN 54-18
- ▶ Made in Italy

## TECHNICAL SPECIFICATIONS

|                            |                                        |
|----------------------------|----------------------------------------|
| Type                       | 3 supervised inputs                    |
| Addresses Occupied on Loop | 3                                      |
| Loop Capacity              | Up to 240 addresses                    |
| Supply Voltage             | 18 ~ 27 VDC                            |
| Stand-by Consumption       | 180 µA                                 |
| Alarm Current              | 6 mA (LED on)                          |
| Status Indicator           | 3-colour LED<br>(red / green / yellow) |
| Dimensions                 | 106 x 54 x 27 mm                       |
| Weight                     | 100 g                                  |
| Humidity                   | 95% RH                                 |

## ORDER DETAILS

- ▶ FF MI250A-3 - Intelligent Addressable 3 Inputs Module With Short Circuit Isolator

FND-DS-FFMI250A-3-EN-REV01