

TX7130 CONVENTIONAL BEAM DETECTOR



EN54-12 CPR CE 

FEATURES

- ▶ Large coverage
- ▶ Smooth operation between 5-100 meters
- ▶ Unmatched suitability for smoke detection
- ▶ Adjustable detector sensitivity
- ▶ Receiver and transmitter in a slot
- ▶ Possibility of economical wiring
- ▶ Laser Alignment Guide
- ▶ EN54-12 Certified
- ▶ LPCB Approved
- ▶ CPR Certificated

TECHNICAL SPECIFICATIONS

- | | |
|-------------------------------|--------------------|
| ▶ Operating Voltage | 20V ~ 28V DC |
| ▶ Operating Current | ≤23mA |
| ▶ Operating Alarm Current | 33mA |
| ▶ LED display | Red, Yellow, Green |
| ▶ Relay Output (Fire / Fault) | Normal Open |
| ▶ NO Contact | 2A 30V DC |
| ▶ Operating Temperature | -5 °C ~ + 55 °C |
| ▶ Storage Temperature | -5 °C ~ + 55 °C |
| ▶ Humidity | ≤95% |
| ▶ Size | 191x127x92 mm |

ORDER DETAILS

- ▶ TX7130 Conventional Beam Detector