

## FF ESF101 ELECTRONIC SOUNDER AND BEACON



CE

EN54-3

Dedal

### FEATURES

- ▶ Modern design eliminates need for device orientation.
- ▶ Superior sound output and low current consumption.
- ▶ Range of installation and base options, for indoor and applications up to IP65.
- ▶ Optimised for 12V and 24V systems, making the range suitable for use in fire & security applications.
- ▶ For use with conventional systems
- ▶ Global tone set: 4 tones including a new bell tone
- ▶ 0,5Hz and 1Hz options

### TECHNICAL SPECIFICATIONS

Voltage Range	24V DC
Alarm Current @24V DC	<30,1mA
Sounder:	
Sound Output	98dB
Number of tones	4
Frequency Range	600-2800Hz
Beacon:	
Flash Rate	1Hz
Flash Color	Red
Environmental:	
Humidity	5% - 95%
Temperature	-10°C to +55°C
Casing	ABS
IP Rating	IP42/IP65 ability

### ORDER DETAILS

- ▶ FF ESF101-A Electronic Sounder and Beacon with shallow base
- ▶ FF ESF101-AB Electronic Sounder and Beacon with shallow base white
- ▶ FF ESF101-B Electronic Sounder and Beacon with deep base
- ▶ FF ESF101-BB Electronic Sounder and Beacon with deep base white