

FF ESF100 + FF LX200

INTELLIGENT ADDRESSED ALARM SOUNDER & BEACON



EN54-3 EN54-23

FEATURES

- ▶ Flexible modular design
- ▶ 5 year product warranty
- ▶ 3rd party approval to EN54-3 and EN54-23
- ▶ 32 Tone Settings
- ▶ Two stage alarm capability
- ▶ Weatherproof as standard
- ▶ Easy to install
- ▶ Silent sounders setting for beacon only use
- ▶ Microphone self test facility
- ▶ Robust and high reliability

TECHNICAL SPECIFICATIONS

- | | |
|--------------------------------------|--------------------|
| ▶ Power supply voltage range | 15Vdc – 40Vdc |
| ▶ Activated current load (High Vol.) | 11-25 mA at 24 Vdc |
| ▶ Acoustic Frequency range | 400-2900 Hz |
| ▶ Maximum acoustic Output | 100 dB(A) @ 1m |
| ▶ Visual Alarm Device Frequency | 0.5 Hz or 1 Hz |
| ▶ Classification | EN54-3 EN54-23 |
| ▶ Temperature range (no icing) | -25°C to +70°C |
| ▶ Max humidity (non condensing) | 95% RH |
| ▶ Protection | IP 65 |

ORDER DETAILS

- ▶ FF ESF100 + FF LX200 Intelligent Addressed Alarm Sounder & Beacon