

FF SMOKE-T

Smoke and Heat Detector Tester







FEATURES

- Smoke and Heat test
- No test gaseous 300 devices test
- Economic, fast and easy test
- Adjustable inspection pole, one button operation
- Using the remote control or smartphone

TECHNICAL SPECIFICATIONS

▶ Testable detector Rate of rise heat detector,

Fixed temperature heat detector

Ionizetion smoke detector, Photoelectric smoke detector, Option: Analog type detector, Option: Unexploded type(Heat)

150mm (Detector insertion) Head size

Minimum 127cm / Maximum 250cm Inspection pole length

2,3 kg ▶ Weight

Material Aluminum, etc.

0 ~ 40°C ▶ Operation temp range

Keeping temp range -10°C to approx. 40°C

Operation humidity range 0 to approx. 85%, No Frost

Smoke generator ability Approx. 1000 tests with 100 ml liquid

Battery 14.8V Li-Ion - Fully charged in about 5 hours

Charger Input:AC 100-240V, 50-60 Hz. Output:DC 12V 2A ▶ Tester ability Approximately 200 heat detectors

(One time of charge) Approximately 300 smoke detectors

Fire & Gas Alarm System • CCTV System • PAVA System

Emergency Lighting System
Access Control System
Integration System

Finder Yangın Güvenlik Elektronik Sistemler A.Ş. Kepez Mah. 5071 Sok. No:10 07090 Kepez / ANTALYA / TURKEY **Tel:**+90 242 259 04 20 Fax:+90 242 259 28 88

















